



All dimensions are in inches.

UNIFIED	Thread Size x Pitch	Type Stainless Steel	Thread Code	Length "L" +.002-.005 (Length Code in 16nds of an inch)								Min. Sheet Thickness	Blind Mounting Hole Diameter +.003/- .000	Min. Depth of Blind Hole	Min. Depth Full Thread F	A Max.	B Max.	C Max.	H +/- .008	Min. Dist. Hole To Edge
				.187	.250	.312	.375	.500	.625	.750	1.00									
.112-40 (#4-40)	DCSS	DCSOS	440	3 <sup>(1)</sup>	4 <sup>(2)</sup>	5 <sup>(2)</sup>	6 <sup>(2)</sup>	8 <sup>(3)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	.062 .093	.213	.043 .075	.188	.041 .072	.165	.212	.250	.188
.138-32 (#6-32)	DCSS	DCSOS	632	3 <sup>(1)</sup>	4 <sup>(1)</sup>	5 <sup>(2)</sup>	6 <sup>(2)</sup>	8 <sup>(3)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	.062 .093	.280	.043 .075	.250	.041 .072	.213	.289	.312	.219
.164-32 (#8-32)	DCSS	DCSOS	832	3 <sup>(1)</sup>	4 <sup>(1)</sup>	5 <sup>(2)</sup>	6 <sup>(2)</sup>	8 <sup>(3)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	.062 .093	.312	.043 .075	.250	.041 .072	.245	.311	.344	.250
.190-32 (#10-32)	DCSS	DCSOS	032	3 <sup>(1)</sup>	4 <sup>(1)</sup>	5 <sup>(2)</sup>	6 <sup>(2)</sup>	8 <sup>(3)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	.062 .093	.344	.043 .075	.375	.041 .072	.290	.343	.375	.281
.250-20 (1/4-20)	DCSS	DCSOS	0420	3 <sup>(1)</sup>	4 <sup>(1)</sup>	5 <sup>(2)</sup>	6 <sup>(2)</sup>	8 <sup>(3)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	.062 .093	.390	.043 .075	.375	.041 .072	.354	.389	.438	.375

All dimensions are in millimeters.

METRIC	Thread Size x Pitch	Type Stainless Steel	Thread Code	Length "L" +0.05-0.13 (Length Code is in millimeters)											Min. Sheet Thickness	Blind Mounting Hole Diameter +0.08/-0.0	Min. Depth of Blind Hole	Min. Depth Full Thread F	A Max.	B Max.	C Max.	H +/- .02	Min. Dist. Hole To Edge
				4 <sup>(1)</sup>	6 <sup>(1)</sup>	8 <sup>(2)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	20 <sup>(3)</sup>	25 <sup>(3)</sup>												
M3x0.5	DCSS	DCSOS	M3	4 <sup>(1)</sup>	6 <sup>(1)</sup>	8 <sup>(2)</sup>	10 <sup>(3)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	20 <sup>(3)</sup>	25 <sup>(3)</sup>	1.6 2.4	5.41	1.10 1.91	5.0	1.04 1.83	4.20	5.39	6.35	4.8			
M4x0.7	DCSS	DCSOS	M4	4 <sup>(1)</sup>	6 <sup>(1)</sup>	8 <sup>(2)</sup>	10 <sup>(2)</sup>	12 <sup>(3)</sup>	16 <sup>(3)</sup>	20 <sup>(3)</sup>	25 <sup>(3)</sup>	1.6 2.4	7.92	1.10 1.91	6.5	1.04 1.83	6.23	7.90	8.74	6.4			
M5x0.8	DCSS	DCSOS	M5	4 <sup>(1)</sup>	6 <sup>(1)</sup>	8 <sup>(3)</sup>	10 <sup>(2)</sup>	12 <sup>(2)</sup>	16 <sup>(3)</sup>	20 <sup>(3)</sup>	25 <sup>(3)</sup>	1.6 2.4	8.74	1.10 1.91	9.6	1.04 1.83	7.37	8.72	9.53	7.2			
M6x1.0	DCSOS		M6	4 <sup>(1)</sup>	6 <sup>(1)</sup>	8 <sup>(3)</sup>	10 <sup>(2)</sup>	12 <sup>(2)</sup>	16 <sup>(3)</sup>	20 <sup>(3)</sup>	25 <sup>(3)</sup>	2.4	9.9	1.91	9.6	1.83	9.0	9.89	11.11	9.5			

- (1) Style #1 Screw length can't exceed the thread depth of the standoff.
- (2) Style #2 Screw will not pass through unthreaded end.
- (3) Style #3 Blind hole