



All dimensions are in inches.

UNIFIED	Thread Size	Type		Thread Code	Length Code "L" ± .015 (Length Code in 16ths of an inch)						Min. Sheet Thickness	Blind Mounting Hole Dia. +.003 -.000	Min. Depth of Blind Hole	A Max.	E ± .010	C Max.	Min. Dist. Hole to Edge	
		Fastener Material			.250	.375	.500	.625	.750	.875								1.00
		Aluminum	Stainless Steel															
.112-40 (#4-40)	DCHA	DCHC	440	4	6	8	10	12	14	-	.062	.172	.043	.041	.205	.171	.156	
	DCFHA	DCFHC		.093	.075	.071												
.138-32 (#6-32)	DCHA	DCHC	632	4	6	8	10	12	14	16	.062	.213	.043	.041	.250	.212	.188	
	DCFHA	DCFHC		.093	.075	.071												
.164-32 (#8-32)	DCHA	DCHC	832	4	6	8	10	12	14	16	.062	.290	.043	.041	.328	.289	.219	
	DCFHA	DCFHC		.093	.075	.071												
.190-32 (#10-32)	DCHA	DCHC	032	-	6	8	10	12	14	16	.062	.312	.043	.041	.350	.311	.250	
	DCFHA	DCFHC		.093	.075	.071												

All dimensions are in millimeters.

METRIC	Thread Size x Pitch	Type		Thread Code	Length Code "L" ± 0.4 (Length Code in Millimeters)						Min. Sheet Thickness	Blind Mounting Hole Dia. +0.08 -0.00	Min. Depth of Blind Hole	A Max.	E ± 0.25	C Max.	Min. Dist. Hole to Edge	
		Fastener Material			6	8	10	12	16	20								-
		Aluminum	Stainless Steel															
M3x0.5	DCHA	DCHC	M3	6	8	10	12	16	20	-	1.60	4.37	1.10	1.04	5.21	4.35	4.00	
	DCFHA	DCFHC		2.40	1.91	1.80												
M4x0.7	DCHA	DCHC	M4	6	8	10	12	16	20	25	1.60	7.37	1.10	1.04	8.33	7.35	5.60	
	DCFHA	DCFHC		2.40	1.91	1.80												
M5x0.8	DCHA	DCHC	M5	-	-	10	12	16	20	25	1.60	7.93	1.10	1.04	8.89	7.90	6.40	
	DCFHA	DCFHC		2.40	1.91	1.80												